

## Description

- 5 **Method, arrangement and set of a plurality of arrangements for eliminating at least one inconsistency in a database collection containing a database and at least one copy database of the database**

10 The invention relates to a method, an arrangement and a set of a plurality of arrangements for eliminating at least one inconsistency in a database collection containing a database and at least one copy database of the database.

- 15 Such a method is disclosed in [1].

In the method disclosed in [1], computers communicate with one another via a communication network using a communication protocol.

20

A communication network is to be understood as meaning, by way of example, a data network, a radio network or else a conventional telephone network.

- 25 A communication protocol is to be understood as meaning a protocol for stipulating the data format used for communication between the computers. Such a communication protocol is the Transport Control Protocol/Internet Protocol (TCP/IP), for example.

30

In the method in [1], a first computer stores a database and each further computer stores a copy of the database, called copy database below.

- 35 The database and the copy databases are modified by a respective computer during a session, i.e. the data contained in the database or in a copy database, or the structure of said data, is modified.

4/744225

In this context, a database is to be understood as meaning a hierarchical or else object-oriented database, for example.

5 A database contains data which is stored in accordance with a prescribed structure and is interrelated. Each object, i.e. each data record within the database, is usually unambiguously identifiable by means of an identifier.

10

Changes to a copy database are sometimes made without the same change also being made in the database itself, or else vice versa.

15 If a consistent database is now meant to be created from the respective copy database and the database, then it is necessary to ascertain and eliminate any inconsistency arising as a result of the data, or the structure of said data, being added, removed or  
20 changed.

An inconsistency is to be understood below as meaning any syntactical difference within a copy database and the database, i.e. any discrepancies arising in the  
25 copy databases and the database between the data elements contained in the database and a copy database, the properties of said data elements and their relationships with one another.

30 [1] indicates various options for eliminating such an inconsistency.

The invention is based on the problem of specifying another method and another apparatus for eliminating  
35 inconsistencies in a database collection which allows an inconsistency to be eliminated whilst saving computation time as far as possible.

The problem is solved by the method, by the arrangement and by the set of a plurality of arrangements having the features of the independent patent claims.

5 The method for the computer-aided elimination of at least one inconsistency in a database collection containing a database and at least one copy database of the database, which inconsistency arises on account of a change in the database and/or in the copy database,  
10 has the following steps:

a) at least some of the operations which can create an inconsistency are allocated to defined conflict types,  
15

b) each conflict type is allocated a decision set which is used to indicate possible decisions which can be used to eliminate an inconsistency created by at least one operation of the respective conflict type,  
20

c) the inconsistency is eliminated using the decision set.

25 The arrangement for eliminating at least one inconsistency in a database collection containing a database and at least one copy database of the database, which inconsistency arises on account of the data in the database or in the copy database being  
30 changed, has at least one processor which is set up such that the following steps can be carried out:

a) at least some of the operations which can create an inconsistency are allocated to defined conflict types,  
35

b) each conflict type is allocated a decision set which is used to indicate possible decisions which

c) the inconsistency is eliminated using the decision set.

15 a) at least some of the operations which can create an inconsistency are allocated to defined conflict types,

b) each conflict type is allocated a decision set which is used to indicate possible decisions which

20 can be used to eliminate an inconsistency created by at least one operation of the respective conflict type,

c) the inconsistency is eliminated using the decision set.

25 The arrangements can be coupled to one another.

30 Preferred developments of the invention can be found in  
the dependent claims.

35

Preferably, in a further embodiment, each conflict type is allocated a decision set which is used to indicate possible decisions which can be used to eliminate an

1. 1. The first  
 2. 2. The second  
 3. 3. The third  
 4. 4. The fourth  
 5. 5. The fifth  
 6. 6. The sixth  
 7. 7. The seventh  
 8. 8. The eighth  
 9. 9. The ninth  
 10. 10. The tenth  
 11. 11. The eleventh  
 12. 12. The twelfth  
 13. 13. The thirteenth  
 14. 14. The fourteenth  
 15. 15. The fifteenth  
 16. 16. The sixteenth  
 17. 17. The seventeenth  
 18. 18. The eighteenth  
 19. 19. The nineteenth  
 20. 20. The twentieth  
 21. 21. The twenty-first  
 22. 22. The twenty-second  
 23. 23. The twenty-third  
 24. 24. The twenty-fourth  
 25. 25. The twenty-fifth  
 26. 26. The twenty-sixth  
 27. 27. The twenty-seventh  
 28. 28. The twenty-eighth  
 29. 29. The twenty-ninth  
 30. 30. The thirtieth  
 31. 31. The thirty-first  
 32. 32. The thirty-second  
 33. 33. The thirty-third  
 34. 34. The thirty-fourth  
 35. 35. The thirty-fifth  
 36. 36. The thirty-sixth  
 37. 37. The thirty-seventh  
 38. 38. The thirty-eighth  
 39. 39. The thirty-ninth  
 40. 40. The fortieth  
 41. 41. The forty-first  
 42. 42. The forty-second  
 43. 43. The forty-third  
 44. 44. The forty-fourth  
 45. 45. The forty-fifth  
 46. 46. The forty-sixth  
 47. 47. The forty-seventh  
 48. 48. The forty-eighth  
 49. 49. The forty-ninth  
 50. 50. The fiftieth  
 51. 51. The fifty-first  
 52. 52. The fifty-second  
 53. 53. The fifty-third  
 54. 54. The fifty-fourth  
 55. 55. The fifty-fifth  
 56. 56. The fifty-sixth  
 57. 57. The fifty-seventh  
 58. 58. The fifty-eighth  
 59. 59. The fifty-ninth  
 60. 60. The sixtieth  
 61. 61. The sixty-first  
 62. 62. The sixty-second  
 63. 63. The sixty-third  
 64. 64. The sixty-fourth  
 65. 65. The sixty-fifth  
 66. 66. The sixty-sixth  
 67. 67. The sixty-seventh  
 68. 68. The sixty-eighth  
 69. 69. The sixty-ninth  
 70. 70. The seventieth  
 71. 71. The seventy-first  
 72. 72. The seventy-second  
 73. 73. The seventy-third  
 74. 74. The seventy-fourth  
 75. 75. The seventy-fifth  
 76. 76. The seventy-sixth  
 77. 77. The seventy-seventh  
 78. 78. The seventy-eighth  
 79. 79. The seventy-ninth  
 80. 80. The eightieth  
 81. 81. The eighty-first  
 82. 82. The eighty-second  
 83. 83. The eighty-third  
 84. 84. The eighty-fourth  
 85. 85. The eighty-fifth  
 86. 86. The eighty-sixth  
 87. 87. The eighty-seventh  
 88. 88. The eighty-eighth  
 89. 89. The eighty-ninth  
 90. 90. The ninetieth  
 91. 91. The ninety-first  
 92. 92. The ninety-second  
 93. 93. The ninety-third  
 94. 94. The ninety-fourth  
 95. 95. The ninety-fifth  
 96. 96. The ninety-sixth  
 97. 97. The ninety-seventh  
 98. 98. The ninety-eighth  
 99. 99. The ninety-ninth  
 100. 100. The hundredth

inconsistency created by a plurality of operations of the respective conflict type.

In addition, in one development, the database  
5 collection contains a plurality of copy databases of the database.

For the purposes of simplification and hence to save  
computation time when eliminating an inconsistency, one  
10 embodiment of the invention provides for all inconsistencies and their dependencies on one another to be ascertained before elimination.

A further saving of the computation time required to  
15 eliminate a plurality of inconsistencies is achieved in a further embodiment by virtue of the decision set for at least one conflict type being modified during elimination of the inconsistencies.

20 In this context, the respective decision set is preferably changed on the basis of dependencies of the inconsistencies.

In one preferred embodiment, after a prescribable  
25 number of eliminated inconsistencies, the database collection is examined for further inconsistencies and their dependency.

In one embodiment, the database collection preferably  
30 contains an object-oriented database.

The method may be used within the context of object-oriented software development or else in the context of  
35 creating a structured electronic document.

An illustrative embodiment of the invention is shown in the figures and is explained in more detail below.

In the figures

202505220504

5 Figure 2 shows a sketch showing computers connected to  
one another via a communication network;

10    Figure 4 shows a tabular overview of possible  
conflicts and decision sets with decision  
options for eliminating the respective  
conflicts.

20 The input/output interface 201 is used to connect the first computer 200 to a screen 205, to a keyboard 206 and to a computer mouse 207.

The first computer 200 stores a database 208.

30 The further computers 210, 220, 230, 240 and 250 each likewise have a processor 213, 223, 233, 243 and 253 and each have a memory 212, 222, 232, 242 and 252. The processor 213, 223, 233, 243 and 253 and the memory  
35 212, 222, 232, 242 and 252 are each connected by means of a respective bus 214, 224, 234, 244 and 254 to the communication network 260 via an input/output interface 211, 221, 231, 241 and 251. In addition, the further computers 210, 220, 230, 240 and 250 are each connected

to a screen 215, 225, 235, 245 and 255 and to a keyboard 216, 226, 236, 246 and 256 and to a computer mouse 217, 227, 237, 247 and 257.

5 A respective copy of the database 208, called copy database 218, 228, 238, 248 and 258 below, is transmitted from the first computer 200 to a respective further computer 210, 220, 230, 240 and 250 and is stored there in the memory 212, 222, 232, 242 and 252  
10 thereof.

Once the copy databases 218, 228, 238, 248 and 258 have been transmitted, the computers 200, 210, 220, 230, 240 and 250 interrupt communication and an independent  
15 change is made among the respective computers 200, 210, 220, 230, 240 and 250, i.e. removal or addition of data or removal or addition of dependencies of the data in a copy database 218, 228, 238, 248 and 258 and in the database 208.

20 Once communication between the first computer 200 and the further computers 210, 220, 230, 240 and 250 is resumed, a consistent database is intended to be formed from the database 208 and the copy databases 218, 228,  
25 238, 248 and 258.

For this purpose, it is necessary to establish respective changes made in the database 208 or in the copy databases in order thus to ascertain  
30 inconsistencies between the copy databases and the database 208 so that the inconsistencies can be eliminated.

Independently of the syntactical structure and of the  
35 dependencies of the data elements on one another, each data element can have an arbitrary number of properties. In this context, each property is of a particular property type and is represented by a current value. For all properties, it is assumed with

0074422 0 2224 460

5

10

- Individual value:

15

## 20

25

- **Ordered listing:**

35

1. 1. The first  
 2. 2. The second  
 3. 3. The third  
 4. 4. The fourth  
 5. 5. The fifth  
 6. 6. The sixth  
 7. 7. The seventh  
 8. 8. The eighth  
 9. 9. The ninth  
 10. 10. The tenth  
 11. 11. The eleventh  
 12. 12. The twelfth  
 13. 13. The thirteenth  
 14. 14. The fourteenth  
 15. 15. The fifteenth  
 16. 16. The sixteenth  
 17. 17. The seventeenth  
 18. 18. The eighteenth  
 19. 19. The nineteenth  
 20. 20. The twentieth  
 21. 21. The twenty-first  
 22. 22. The twenty-second  
 23. 23. The twenty-third  
 24. 24. The twenty-fourth  
 25. 25. The twenty-fifth  
 26. 26. The twenty-sixth  
 27. 27. The twenty-seventh  
 28. 28. The twenty-eighth  
 29. 29. The twenty-ninth  
 30. 30. The thirtieth  
 31. 31. The thirty-first  
 32. 32. The thirty-second  
 33. 33. The thirty-third  
 34. 34. The thirty-fourth  
 35. 35. The thirty-fifth  
 36. 36. The thirty-sixth  
 37. 37. The thirty-seventh  
 38. 38. The thirty-eighth  
 39. 39. The thirty-ninth  
 40. 40. The fortieth  
 41. 41. The forty-first  
 42. 42. The forty-second  
 43. 43. The forty-third  
 44. 44. The forty-fourth  
 45. 45. The forty-fifth  
 46. 46. The forty-sixth  
 47. 47. The forty-seventh  
 48. 48. The forty-eighth  
 49. 49. The forty-ninth  
 50. 50. The fiftieth  
 51. 51. The fifty-first  
 52. 52. The fifty-second  
 53. 53. The fifty-third  
 54. 54. The fifty-fourth  
 55. 55. The fifty-fifth  
 56. 56. The fifty-sixth  
 57. 57. The fifty-seventh  
 58. 58. The fifty-eighth  
 59. 59. The fifty-ninth  
 60. 60. The sixtieth  
 61. 61. The sixty-first  
 62. 62. The sixty-second  
 63. 63. The sixty-third  
 64. 64. The sixty-fourth  
 65. 65. The sixty-fifth  
 66. 66. The sixty-sixth  
 67. 67. The sixty-seventh  
 68. 68. The sixty-eighth  
 69. 69. The sixty-ninth  
 70. 70. The seventieth  
 71. 71. The seventy-first  
 72. 72. The seventy-second  
 73. 73. The seventy-third  
 74. 74. The seventy-fourth  
 75. 75. The seventy-fifth  
 76. 76. The seventy-sixth  
 77. 77. The seventy-seventh  
 78. 78. The seventy-eighth  
 79. 79. The seventy-ninth  
 80. 80. The eightieth  
 81. 81. The eighty-first  
 82. 82. The eighty-second  
 83. 83. The eighty-third  
 84. 84. The eighty-fourth  
 85. 85. The eighty-fifth  
 86. 86. The eighty-sixth  
 87. 87. The eighty-seventh  
 88. 88. The eighty-eighth  
 89. 89. The eighty-ninth  
 90. 90. The ninetieth  
 91. 91. The ninety-first  
 92. 92. The ninety-second  
 93. 93. The ninety-third  
 94. 94. The ninety-fourth  
 95. 95. The ninety-fifth  
 96. 96. The ninety-sixth  
 97. 97. The ninety-seventh  
 98. 98. The ninety-eighth  
 99. 99. The ninety-ninth  
 100. 100. The hundredth



5     The criterion for the order is defined by an  
application program, and the observance of the order  
criteria is also monitored by the latter. An example  
of this property type is an indexed list containing  
arbitrary entries (e.g. text document), in which each  
10    line or each character corresponds to one entry.

15    **Data element**

```
DE def (ID, infospace, elementtype, properties);
```

- ```
25 • properties  $\subseteq \{(\text{name}, \text{propertytype}, \text{value}):$ 
```

MEN is a quantity of all the property names and the following applies:

MEW is a quantity of all the property values, and

```
35 {"value", "listing", "ordered listing"}.
```

In addition, an information space is defined as follows:

An information space IR is a 3-tuple  
IR def (ID, irname, owner, data)

- ID is a one-to-one identifier throughout the system, where the following applies:  
 $\forall i \in (1, \dots, n); \forall k \in (1, \dots, n): i \neq k:$   
 $IR_i.ID \neq IR_k.ID;$

- $irname \in MIRR$   
 where the following applies:  
 $\forall i \in (1, \dots, m); \forall k \in (1, \dots, m): i \neq k:$

- owner =  $N_i$  where  $N_i \in MN$  or  $N_{gi}$  where  $N_{gi} \in MNG$ ;
- data is the data which can be accessed by a user group and is associated with the IR.

## Relationship between data elements

```
30 BZ def (relationshiptype, name, dataelement1,
dataelement2)
```

```

35  • relationshiptype ∈ MBT; where MBT is a quantity of
    all the relationship types
    {"undirected", "logical", "successor", "subsup"}
    • dataelement1, 2 ∈ MDE; where MDE is a quantity of all
    the data elements.

```

In order to ascertain inconsistencies, each computer 200, 210, 220, 230, 240 and 250 carries a respective protocol relating to all the operations carried out on the database or on the respective copy database and stores it in the form of a list.

The stored list is called the history below.

Hence, the database 208 and each copy database 218, 228, 238, 248 and 258 have a respective associated history.

This situation is shown in Figure 3. Figure 3 shows the database 301 containing objects 302, 303, 304 and 305 and also a history 306 storing, as entries 307, 308, 309, change operations which have been carried out on the database 301 by the first computer 200 since communication with the further computers 210, 220, 230, 240 and 250 was interrupted. The entries 307, 308, 309 are likewise stored in the memory 202 of the first computer 200.

A first copy database 310 containing objects 311, 312, 313 and 314 likewise has an associated history 315 with appropriate change operations 316, 317, 318. The copy database 310 is stored in the further computer 210.

A second copy database 320 containing objects 321, 322, 323 and its associated history 325 with change operations 326, 327, 328 is stored in a further computer 220.

To form the consistent database, i.e. to reintegrate all the copy databases 218, 228, 238, 248 and 258 with the database 208, the histories 315, 325, ... are transmitted to the first computer 200 via the communication network 260 and are stored in the memory 202 of the first computer 200.

5

10 In addition, the following change operations are taken into account and are used to uniquely describe the inconsistencies which have arisen.

### 1. Create Element:

```
createElement(ir, id, elementtype) RETURN R(IR)
BEGIN element := instantiate(elementtype)
    element.elementname:= id
    R(ir):= insert(R(ir).data,element)
    R(ir):= add(R(ir).history,
        "createElement(id,elementtype)")
    return R(ir)
```

30

This operation creates a data element of the data type **elementtype** with the identifier **id** in a copy database **R(ir)** within an information space **ir**, to which this operation is applied. In this context, all the properties of the newly created data element receive a preset initialization value. Having been initialized, the new element is added under the specified name to the data in the copy database **R(ir)** and the executed operation is added without the information space as a

parameter into the history **R(ir).history** associated with the copy database. In this context, the unique identifier **id** can be created by the application sending the operation.

5

## 2. DeleteElement:

**DeleteElement**(R(IR), ID) → R(IR)

**deleteElement**(ir, id) RETURN R(IR)

```

10      BEGIN element := select (R(ir).data, id)
          R(ir) := remove(R(ir).data, element)
          R(ir) := add(R(ir).history, "deleteElement(id)")
          return R(ir)
      END

```

15

This operation deletes a data element with the name **id** from the copy database **R(ir)** of the information space **ir** and writes the executed operation into the history **R(ir).history** associated with the copy database. All the properties of the data element which have been modified since the instantiation of the data element are also lost in the process. The relationships affecting the element are retained, however. If these are likewise to be deleted, then the application program is responsible for this.

25

## 3. ChangeProperty:

**ChangeProperty**(R(IR), ID, Property type, Value) → R(IR)

30

```

changeProperty(ir, id, propname, newValue) RETURN R(IR)
      BEGIN element := select (R(ir).data, id)
          property := select(element.properties,
                               propname)
          property.value := newValue
35      R(ir) := add (R(ir).history, "changeProperty
          (id, propname, newValue)")
          return R(ir)
      END

```

This operation sets the value of the property **propname** of the data element with the identifier **id** to the value **newValue** in the copy database **R(ir)** of the information space **ir** and writes the executed operation into the history **R(ir).history** associated with the copy database.

#### 4. ChangePropertyAdd:

```

ChangePropertyAdd(R(IR), ID, Property type, Entry) → R(IR)
10
changePropertyAdd(ir, id, propname, newEntry) RETURN R(IR)
    BEGIN element := select (R(ir).data, id)
        property := select (element.properties,
        propname)
15        add (property.value, newEntry)
        R(ir) := add(R(ir).history,
        "changePropertyAdd (id, propname,
        newEntry)")
        return R(ir)
20    END

```

This operation is for properties of the "listing" type. The operation adds a new entry **newEntry** to the copy database **R(ir)** of the information space **ir** in the value of the property **propname** of the data element with the identifier **id** at the end of the listing. The executed operation is then stored in the history **R(ir).history** associated with the copy database.

#### 30 5. ChangePropertyDel:

```

ChangePropertyDel(R(IR), ID, Property type, Index,
    Entry) → R(IR)

changePropertyDel(ir, id, propname, index, oldEntry)
35    RETURN R(IR)
    BEGIN element := select (R(ir).data, id)
        property := select (element.properties,
        propname)
        del (property.value, oldEntry)

```

00744222 042204

5                   END

10

15

$$\text{ChangePropertyInsert}(R(IR), ID, \text{Property type}, \text{Index}, \text{Number}, \text{Entries}) \rightarrow R(IR)$$

20

25

30

35

identifier **id** from the position **Index** in the ordered listing **Property.Value**. For all the entries in the ordered listing **property.Value** having an identical index to or a larger index than **index**, **index** is increased by the value **number**. The executed operation is then stored in the history **R(ir).history** associated with the respective copy database.

#### 7. ChangePropertyRemove:

```

10  ChangePropertyRemove(R(IR), ID, Property type, Index,
      Number, Entries) → R(IR)

      changePropertyRemove(ir, id, propname, index, number,
                           oldEntries) RETURN R(IR)
15      BEGIN element := select (R(ir).data,id)
           property := select (element.properties,
                               propname)
           for (i=0, i < number, i++){
           remove (property.value.index, oldEntries.
20             (i+1))
           decrIndex (property.value.entries, ind >
           index)}
           R(ir) := add(R(ir).history,
           "changePropertyRemove(id, propname, index,
25             number, oldEntries)")
           return R(ir)

      END

```

A property to which this operation can be applied is of the "ordered listing" type. This operation deletes the entries **oldEntries** in the copy database **R(ir)** of the information space **ir** in the value of the property **propname** of the data element with the identifier **id** from the position **Index** in the ordered listing **Property.Value**. All entries with a larger index than (**index + number**) have their index reduced by the value **number**. The executed operation is then stored in the history **R(ir).history** associated with the respective copy database.

"ordered listing" type



**8. CreateRelationship:**

**CreateRelationship**(R(IR), Name, Relationship type,  
ID1, ID2) → R(IR)

```

5  createRelationship(ir, name, reltype, fromid, toid,
                        toidir) RETURN R(IR)
      BEGIN relationship := instantiate (reltype)
        relationship.name := name
        relationship.dataelement1 := fromid
10     relationship.dataelement2 := toid
        relationship.dataelement2.ir := toidir
        R(ir) := insert (R(ir).data, relationship)
        R(ir) := add (R(ir).history,
15     "createRelationship (name, reltype, fromid,
        toid, toidir)")
        return R(ir)
      END

```

20 This operation creates a relationship of the **reltype** type between the data elements with the identifiers **fromid** and **toid** under the name **name** and adds the new relationship to the data in the copy database **R(ir)** of the information space **ir**. The executed operation is then stored in the history **R(ir).history** associated

25 with the copy database. It is assumed for all relationships that, for each relationship name allocated, there is only a single relationship of the same type between two data elements. If a plurality of relationships of the same type are necessary under the

30 same name between two data elements, then identifiers need to be introduced for relationships as well. However, the assumption made is sufficient for the majority of applications. The information space of the target data element need be specified only in the case

35 of a logically externally directed relationship.

09744226 012204  
102210 522460

**9. DeleteRelationship:**

**DeleteRelationship**(R(IR), Name, Relationship type, ID1,  
ID2)→R(IR)

**deleteRelationship**(ir, name, reltype, fromid,  
5 toid.toidir)

RETURN R(IR)

BEGIN relationship := select (R(ir).data, name,  
reltype, fromid, toid)

R(ir) := remove (R(ir).data, relationship)  
10 R(ir) := add (R(ir).history,  
"deleteRelationship (name, reltype, fromid,  
toid.toidir)")  
return R(ir)

END

15

This operation deletes a relationship of the **reltype** type between the data elements with the identifiers **fromid** and **toid** under the name **name** from the copy database **R(ir)** of the information space **ir**. The  
20 executed operation is then stored in the history **R(ir).history** associated with the copy database. The information space of the target data element need be specified only for the relationships of the logically externally directed type.

25

In a further step, all conflicts, dependencies, anomalies, pseudo-anomalies and restrictions by dependencies are recognized (step 103).

30 A conflict is to be understood as meaning the smallest decidable quantity of operations which arise only on one side in syntactical terms, uniquely describe an inconsistency and can be meaningfully presented to a user or to the system and eliminated (decided) by the  
35 latter.

Each conflict can be recognized as a whole and can be resolved by a single decision during reintegration.

reintegrated

5 A distinction is drawn between harmless conflicts and  
critical conflicts.

Harmless conflicts (HK) contain only operations which describe modifications on one copy database. In this case, there is therefore just one user desiring and making a change to the part of the data structure or the copy database or else the database itself. The operations carried out are thus complemented. Depending on which copy database is to be allocated the operation or operations, when the copy databases of users A and B are present, harmless conflicts with operations on the copy database of a first user A can be referred to as HKA and harmless conflicts with operations on the copy database of a second user B can be referred to as HKB, on a general basis.

By contrast, critical conflicts (KK) contain changes on both sides to the same part of the data structure and represent contrary views of the users about the ultimate state of particular data within the database and copy databases. In this context, a critical conflict can also be defined by different operations on two copy databases. In such cases, a distinction is drawn between a critical conflict KKA and a critical conflict KKB.

Formally, a conflict is defined as follows:

**Conflict:**

35 A conflict K between two histories EHA and EHB and a  
common history GH is a 6-tuple  
K(EHA, EHB, GH) def

```
(id, ktype, operationsEHA, operationsEHB,
```

7

- 15

## 1. First harmless conflict HK1:

There is a creation operation for a data element `createElement(id, elementtype)` in one history only.

$$\text{HK1B} = \text{createElement}(\text{id}, \text{elementtype}) \in \text{EHB}.$$

```
HK2 = (deleteElement/ -- )
```

$$\text{HK2A} = \text{deleteElement}(\text{id}, \text{elementtype}) \in \text{EHA} \vee$$

3. Third harmless conflict HK3:

There is a creation operation for a relationship `createRelationship (reltype, rname, id1, id2)` in one history only.

$$\text{HK3B} = \text{createRelationship}(\text{reltype}, \text{rname}, \text{id1}, \text{id2}) \in \text{EHB}.$$

## 5

10

15

20

10

15

20

25

30

There are  $n$  ( $n$  is an element of the natural numbers and  $n > 0$ ) insertion operations `changePropertyAdd(id, name, entry)` with the same entry **entry** for the same property of the "listing" type for a data element in one history, with there being no deletion operation with the same entry for the same property of the data element in another history. The inconsistency described consists in the fact that there are  $n$  entries of the

type **entry** more in the copy database with the creation operations in the history associated with the copy database than in the other copy database.

HK7A = n times changePropertyAdd(id,name,entry)  $\in$  EHA  $\vee$

5 HK7B = n times changePropertyAdd(id,name,entry)  $\in$  EHB.

#### 8. Eighth harmless conflict HK8:

HK8 = (n x changePropertyDel/ -- )

There are n (n is an element of the natural numbers) deletion operations changePropertyDel(id, name, entry) with the same entry **entry** for a property of the "listing" type for a data element in one history, with there being no insertion operation with the same entry for the property of the data element in another history. The inconsistency described consists in the fact that the n entries of the type **entry** are present to a lesser extent in the copy database whose history contains the deletion operations than in the other copy database.

20 HK8A = n times changePropertyDel(id,name,entry)  $\in$  EHA  $\vee$

HK8B = n times changePropertyDel(id,name,entry)  $\in$  EHB.

#### 9. Ninth harmless conflict HK9:

HK9 = (changePropertyInsert/ -- )

25 There is an insertion operation changePropertyInsert(id, name, index1, 1, entry1) for an index with an individual entry for a property of the "ordered listing" type for a data element in one history only, with another history containing no insertion operations with another entry for a checkable identical index for the same property of the data element.

30 HK9A = changePropertyInsert(id,name,index,1,entry)  
 $\in$  EHA  $\vee$

HK9B = changePropertyInsert(id,name,index,1,entry)  
35  $\in$  EHB.

#### 10. Tenth harmless conflict HK10:

HK10 = (changePropertyRemove/ -- )

There is a deletion operation

094425-04304  
F0210 22460

changePropertyRemove(id, name, index1, 1, entry1) for an index with an individual entry for a property of the "ordered listing" type for a data element in one history only.

- 5 HK10A = changePropertyIRemove(id,name,index,1,entry)  
           ∈ EHA ∨  
 HK10B = changePropertyIRemove(id,name,index,1,entry)  
           ∈ EHB.

10 **11. Eleventh harmless conflict HK11:**

HK11 = (changePropertyRemove,changePropertyInsert/--)

There is a deletion operation

- changePropertyRemove(id, name, index1, 1, entry1) for an index **index** with an individual entry for a property of the "ordered listing" type for a data element, and a subsequent creation operation

- changePropertyInsert (id, name, index1, 1, entry2) for an entry for the same index for the same property of the same data element in one history only.

- 20 HK11A = [changePropertyIRemove(id,name,index,1,entry1),  
           changePropertyIInsert(id,name,index,1,entry2)]  
           ∈ EHA ∨  
 HK11B = [changePropertyIRemove(id,name,index,1,entry1),  
           changePropertyIInsert(id,name,index,1,entry2)]  
 25        ∈ EHB.

The following text gives an overview of critical conflicts (KK), i.e. operations in a plurality of histories:

30

**1. First critical conflict KK1:**

KK1 = (createRelationship12/ createRelationship13)

There is a creation for a relationship

- createRelationship(reltype, rname, id1, id2) in one history, with a creation  
 35 createRelationship(reltype, rname, id1, id3) for the same relationship (reltype, rname), starting from the same source data element but to another target data element, existing in another history.

10220 524450

$$\text{KK1} = \text{createRelationship}(\text{reltype}, \text{rname}, \text{id1}, \text{id2}) \in \text{EHA} \wedge \\ \text{createRelationship}(\text{reltype}, \text{rname}, \text{id1}, \text{id3}) \in \text{EHB}.$$

## 2. Second critical conflict KK2:

```
5  KK2 = (deleteRelationship12, createRelationship13 /
        deleteRelationship12, createRelationship14)
```

The different change in a relationship can be recognized in the histories like the first critical conflict KK1. In addition, however, a common history GH contains a deletion `deleteRelationship(reltype, rname, id1, id2)` for the common relationship `(rname, reltype)` from the same source data element, but to another target data element.

$$\begin{aligned} \text{KK2} &= \text{deleteRelationship}(\text{reltype}, \text{rname}, \text{id1}, \text{id2}) \in \text{GH} \wedge \\ &\quad \text{createRelationship}(\text{reltype}, \text{rname}, \text{id1}, \text{id3}) \in \text{EHA} \wedge \\ 15 \quad &\quad \text{createRelationship}(\text{reltype}, \text{rname}, \text{id1}, \text{id4}) \in \text{EHB}. \end{aligned}$$

### 3. Third critical conflict KK3:

```
KK3 = (deleteRelationship12, createRelationship13/  
deleteRelationship12)
```

20 A relationship's modification on one side and deletion on  
the other side can be recognized in the histories, like  
the third harmless conflict HK3, by an operation  
createRelationship(reltype, rname, id1, id3). In  
addition, however, the common history contains a deletion  
25 deleteRelationship (reltype, rname, id1, id2) for the  
common relationship (rname, reltype) from the same source  
data element but to the last common target data element.

$$\text{KK3A} = \text{deleteRelationship}(\text{reltype}, \text{rname}, \text{id1}, \text{id2}) \in \text{GH} \wedge \\ \text{createRelationship}(\text{reltype}, \text{rname}, \text{id1}, \text{id3}) \in \text{EHA};$$
$$30 \quad \text{KK3B} = \text{deleteRelationship}(\text{reltype}, \text{rname}, \text{id1}, \text{id2}) \in \text{GH} \wedge \\ \text{createRelationship}(\text{reltype}, \text{rname}, \text{id1}, \text{id3}) \in \text{EHB}.$$

#### 4. Fourth critical conflict KK4:

KK4 = (changeProperty/ changeProperty)

```

35  There is a change operation
    changeProperty (id, name, valuenew1, valueold) for a
    property of the "value" type for a data element in one
    history, with another change operation existing in

```



another history for the same property of the data element.

$$\text{KK4} = \text{changeProperty}(\text{id}, \text{name}, \text{valuenew1}, \text{valueold}) \in \text{EHA} \wedge \\ \text{changeProperty}(\text{id}, \text{name}, \text{valuenew2}, \text{valueold}) \in \text{EHB}.$$

5

5. Fifth critical conflict KK5:

$$KK5 = (n \text{ changePropertyAdd} / m \text{ changePropertyDel})$$

There are  $n$  ( $n$  is an element of the natural numbers) identical operations of the type

10    `changePropertyAdd(id, name, entry)` with the same entry  
for a property of the "listing" type for a data element  
in one history, with another history  $m$  ( $m$  is an element  
of the natural numbers) containing identical operations  
of the type

15 changePropertyDel(id, name, entry) with the same entry  
for the same property of the data element. The  
inconsistency described consists in the fact that the  
copy database with the creation operations in the history  
associated with the copy database contains  $n + m$   
20 identical entries entry more than the other copy  
database. To be able to make an exact statement about the  
occurrence of the operations, a distinction is drawn for  
the fifth critical conflict KK5 between a fifth critical  
conflict of first type KK5A and a fifth critical conflict  
25 of second type KK5B. In this case, the allocation is made  
using the creation operations.

$$\text{KK5A} = (\text{n changePropertyAdd}(\text{id}, \text{name}, \text{entry}) \in \text{EHA} \wedge \\ \text{m changePropertyDel}(\text{id}, \text{name}, \text{entry}) \in \text{EHB} \vee$$
$$\begin{aligned} \text{KK5B} = & (\text{m changePropertyDel}(\text{id}, \text{name}, \text{entry}) \in \text{EHA}; \\ & \text{n changePropertyAdd}(\text{id}, \text{name}, \text{entry}) \in \text{EHB}. \end{aligned}$$

**6. Sixth critical conflict KK6:**

```
KK6 = (changePropertyInsert / changePropertyInsert)
```

There is an insertion operation

```
35  changePropertyInsert(id, name, index1, 1, entry1) for
    an index with an individual entry for a property of the
    "ordered listing" type for a data element in one
    history, with another history containing an insertion
```

operation with another entry for the same (this can be checked) index for the property of the data element.

KK6 = changePropertyInsert(id,name,index1,1,entry1)  
 $\in \text{EHA} \wedge$

5 changePropertyInsert(id,name,index2,1,entry2)  
 $\in \text{EHB}.$

#### 7. Seventh critical conflict KK7:

KK7 = (changePropRemove, changePropInsert /  
 10 changePropRemove, changePropInsert)

The different change on the two sides in an individual entry on a common index **index** for a property of the "ordered listing" type for a data element can be recognized in the histories like the sixth critical  
 15 conflict KK6. In addition, however, the common history contains a changePropertyRemove(id, name, index1, 1, entry1) operation for the last common entry on the same (this can be checked) index.

KK7 = changePropertyRemove(id,name,index1,1,entry1)  
 20  $\in \text{GH} \wedge$   
 changePropertyInsert(id,name,index2,1,entry2)  
 $\in \text{EHA} \wedge$   
 changePropertyInsert(id,name,index3,1,entry3)  
 $\in \text{EHB}.$

25

#### 8. Eighth critical conflict KK8:

KK8 = (changePropRemove, changePropInsert /  
 changePropRemove)

The change, on one side, and deletion, on the other  
 30 side, in/of an individual entry on a common index **index** for a property of the "ordered listing" type for a data element in the histories can be recognized like a tenth harmless conflict HK10. In addition, however, the common history contains a

35 changePropertyRemove(id, name, index1, 1, entry1)  
 operation for the last common entry on the same (this can be checked) index.

KK8A = changePropertyRemove(id,name,index1,1,entry1)  
 $\in \text{GH} \wedge$

1990-2000

```

      changePropertyInsert(id,name,index2,1,entry2)
      ∈ EHA;
KK8B = changePropertyRemove(id,name,index1,1,entry1)
      ∈ GH ∧
5      changePropertyInsert(id,name,index2,1,entry2)
      ∈ EHB.

```

10 The operations stored in the histories describe the autonomously modified data areas directly and are used to describe and to eliminate (described below) the inconsistencies.

To recognize the inconsistencies, two respective histories are compared with one another.

15 The inconsistencies are recognized at the start of the method, before the actual reintegration.

20 The search for the existing inconsistencies in the copy databases by searching for conflict operations is carried out in the three steps described below.

25 • A first step makes a pass through the two histories to be compared with one another in the copy databases and in the database, which are to be matched to one another. All the operations in the histories are allocated, separately on each side, to a respective one of the new operation collections (createElement operations, deleteElement operations, createRelationship operations, deleteRelationship operations, changeProperty operations, changePropertyAdd operations, changePropertyDel operations, changePropertyInsert operations and changePropertyRemove operations) described above.

35 • In a second step, a respective conflict register KR is started for each conflict type described above HK1A, ..., HK11A, HK1B, ..., HK11B, KK1, KK2, KK3A, KK3B, KK4, KK5A, KK5B, KK6, KK7, KK8A, KK8B. In this

FOR "SECRET"

context, it is ensured that all conflicts for which operations from the two histories contribute to the respective conflict are not recognized twice and stored in the respective conflict register KR twice.

5 Accordingly, the operation collections just formed are searched through on the basis of the definitions of the conflict types, as described above, starting with the first harmless conflict HK1A in the history of the first user A. If a conflict has been

10 ascertained, the conflict is stored in the conflict register KR for the appropriate conflict type, for example the first harmless conflict HK1 is stored in the copy database of the first user A in a conflict register KR\_HK1A.

15

- If the search and storage of the conflicts has taken place, the operation collections created at the start are deleted again in a third step. The subsequent elimination of the inconsistencies is based on the

20 conflicts stored in the conflict registers KA and on the operations of said conflicts.

A conflict register KR is defined as follows:

25 **Conflict register KR:**

A conflict register KR for two histories EHA and EHB and a common history GH is a 2-tuple

$KR(EH_A, EH_B, GH) \underline{def} (crtype, conflictids)$

30

- $crtype \in \{KA\_HK1A, \dots, KA\_HK11A, KA\_HK1B, \dots, KA\_HK11B, KA\_KK1, KA\_KK2, KA\_KK3A, KA\_KK3B, KA\_KK4, KA\_KK5A, KA\_KK5B, KA\_KK6, KA\_KK7, KA\_KK8A, KA\_KK8B\}$
- conflictids are identifiers for all the conflicts

35  $K(EH_A, EH_B, GH)$  associated with the conflict register KR, where K.type can be allocated to the respective conflict array type KR.crtype.

An anomaly is present when two data elements exist in the two copy databases before and after the division

102210" 2224460

5

10

An anomaly is defined as follows:

### Anomaly:

15

```
AM(K1, K2) def (id, amtype, cid1, cid2)
```

20

25

**Anomaly register AMR:**

30

AMR (EHA, EHB, GH) def (anomalyids)

35

Pseudo-anomalies describe situations in which the occurrence of an anomaly from conflicts which are

present can be prevented only through targeted minimization of the decision options for the conflicts.

A pseudo-anomaly is defined as illustrated below:

5

**Pseudo-anomaly PAM:**

A pseudo-anomaly PAM between two conflicts K1(EHA, EHB, GH) and K2(EHA, EHB, GH) is a 4-tuple

10 PAM(K1, K2) def (id, pamtype, cid1, cid2)

- id is a one-to-one identifier throughout the system (see also definition of a data element)
- pamtype  $\in$  {pseudo-Anomaly1A, ..., pseudo-Anomaly32AB}
- 15 • cid1 = K1.id
- cid2 = K2.id.

A pseudo-anomaly register PAMR is defined as follows:

20 **Pseudo-anomaly register PAMR:**

A pseudo-anomaly register PAMR for two histories EHA and EHB and a common history GH is a 1-tuple

PAMR(EHA, EHB, GH) def (pseudo-anomalyids)

25

- Pseudo-anomalyids are the identifiers for all pseudo-anomalies between the histories EHA and EHB and the common history GH.

30 After the conflicts have been ascertained, each ascertained conflict is resolved by means of a respective individual decision. The conflict resolution process thus comprises a sequence of conflict resolution decisions.

35

The conflict resolution is denoted in **Figure 1** by step 104.

In principle, there are various decision options:

a) Adopt the conflict operation(s)

SECRET

- b) Reject the conflict operation(s)
- c) Partly adopt, partly reject the conflict operation(s)
- d) Reject the conflict operation(s), adopt new created operation(s).

5

The individual conflict types are allocated a decision set ES, the decision set ES containing possible decisions which can be used to eliminate an inconsistency created by an operation of the respective conflict type, to which a respective decision set ES is allocated.

10

**Figure 4** compiles all the decision sets which are allocated to a respective conflict.

15

Each row of the table shown in **Figure 4** shows a possible decision option E1, E2, E3a, E3b, E4, E5a, E5b, E6.

20 In each case, an x in a field denotes that the conflict shown in the respective column can be resolved by a decision option which is shown in the respective row.

The following text gives an overview of the possible decision options:

25

A first decision option E1 describes the adoption of a conflict operation or of a plurality of conflict operations.

30

A conflict operation describes all the data operations associated with a conflict. Adopt is understood to mean that the conflict operations are executed in the copy database in which they have not yet been carried out.

35

A second decision option E2 describes the rejection of a conflict operation or a plurality of conflict operations.

A third decision option E3 describes the adoption of one or more conflict operation(s) in one copy database and the rejection of the conflict operation(s) in the other copy database.

5

For the third decision option E3, a detail decision is provided which defines which of the conflict operations present in the histories of different copy databases of the users A and B are to be adopted and which are to be rejected.

10

These decision options are denoted as a first part E3a of the third decision option E3 and as a second part E3b of the third decision option E3. The first part E3a of the third decision option E3 describes the adoption of the conflict operation(s) in the copy database of the first user A and the rejection of the conflict operation(s) in the copy database of the second user B. The second part E3b of the third decision option E3 describes the adoption of the conflict operation(s) of the copy database of the second user B and the rejection of the conflict operation(s) of the copy database of the first user A.

15

20

25 As **Figure 4** shows, a first decision set ES1, which is allocated to the first harmless conflict HK1, describes the first decision option E1 and the second decision option E2 to eliminate the first harmless conflict HK1.

30 A second decision set ES2 is allocated to the second harmless conflict HK2 and again contains the first decision option E1 and the second decision option E2 to eliminate the second harmless conflict HK2.

35 If the previous resolution options through the adoption or rejection of available conflict operations do not correspond to the target ideas of the users with regard to the ultimate reintegrated database, i.e. the users A and B cannot agree on one state described by the

2025 RELEASE UNDER E.O. 14176



conflicts, then there is the option of adopting an intermediate solution or the option of selecting and adopting new operations not contained in the decision set. The two options will be illustrated below.

5

For a conflict with a number  $n$  of identical operations, defining the conflict, from a set of data operations in only one history (conflicts of the type HK7 II and HK8 II), there are generally selection options for intermediate states, as described below.

10

For the seventh harmless conflict HK7 with  $n = 1$ , HK7 I is written below, and HK7 II is written below for the seventh harmless conflict HK7 with  $n > 1$ . For the eighth harmless conflict HK1 with  $n = 1$ , HK8 I is written below, and HK8 II is written below for the eighth harmless conflict HK8 with  $n > 1$ .

15

In this context, a fourth decision option E4 describes a partial adoption and partial rejection of the conflict operations.

20

For the fourth decision option E4, a more precise statement is provided which defines how many of the conflict operations arising on one side are to be adopted and how many are to be rejected. For a number of  $n$  operations ( $n$  is the element of the natural numbers), the decision options extend from adoption of one operation and rejection of  $n-1$  operations up to adoption of  $n-1$  operations and rejection of one operation. In this case, an adequate decision option is to define the number  $k$  ( $0 < k < n$ ) of adopted operations. The number of rejected operations is then calculated from  $n - k$ . The fourth decision option E4 can thus be specialized as follows: the fourth decision option E4 describes the number of adopted conflict operations  $k$ .

25

30

35

T0220"2222222222

In addition, the fifth critical conflict KK5 with  $n = m = 1$  is denoted by KK5 I below and the fifth critical conflict KK5 with  $n > 1$  and  $m > 1$  is denoted by KK5 II below.

5

For a fifth critical conflict KK5 II with a number  $n$  of identical operations `changePropertyAdd`, defining the conflict, in one copy database and a number  $m$  of identical operations `changePropertyDel`, defining the conflict, in another copy database, selection of the intermediate states is more difficult.

Since the operations defining the conflict in one history and the operations involved in the conflict in the other history cancel one another out, the same end result can be obtained by means of different decision options.

Thus, resetting a `changePropertyAdd` operation and adopting a `changePropertyAdd` operation in one copy database in conjunction with resetting a `changePropertyDel` operation in another copy database can obtain the same result as adopting two `changePropertyAdd` operations in one copy database and a `changePropertyDel` operation in the other copy database. So that all decision options between the extremes of rejecting the operations in one copy database and adopting the operations in the other copy database (third decision option E3a/E3b) are provided, but various decision options are at the same time prevented from supplying an identical result, there is the solution option of the fifth decision option E5, as illustrated below.

The fifth decision option E5 can create the last common state between the copy databases by rejecting all operations and permits all other final states from the combinations of the operations, but without the conflict states present above.

The fifth decision option E5 thus describes the partial adoption and partial rejection of the conflict operations in one copy database and the rejection of the conflict operations in another copy database.

5

For the fifth decision option E5, the decision sub-options are necessary, which firstly define which copy database is affected by the partial adoption and partial rejection and which database is affected by the total rejection, and secondly how many of the conflict operations are to be adopted in the case of partial adoption and how many are to be rejected. In this case, the number of operations during partial adoption and partial rejection can be defined as in the case of the fourth decision option E4 using the sole definition of the number of adopted operations. The number of adopted operations in a first copy database of the first user A is in this case denoted by  $i$ , and the number of adopted operations in the copy database of the second user B is denoted by  $k$ . Thus, detail decisions for the fifth decision option E5 are:

First part E5a of the fifth decision option E5:  
Number of adopted conflict operations for the copy database of the first user A:  
( $1 < i < n$ ) if a changePropAdd operation is involved,  
( $1 < k < m$ ) if a changePropDel operation is involved,  
and rejection of all conflict operations for the copy database of the second user B.

30

Second part E5b of the fifth decision option E5:  
Number of adopted conflict operations for the copy database of the second user B:  
( $1 < i < n$ ) if a changePropAdd operation is involved,  
( $1 < k < m$ ) if a changePropDel operation is involved,  
and rejection of all conflict operations for the copy database of the first user A.

35

2025 RELEASE UNDER E.O. 14176

A selection option for creating a new state for the conflict will be defined by the decision options below.

5 In general, the option of creating and selecting a state which differs from the two available versions is provided for all conflicts apart from for the conflicts of type HK1, HK2, HK4, HK10.

10 For creating a new state, it is necessary to create a common starting position, i.e. the relevant operation(s) must be rejected and the two copy databases must be made consistent in terms of the data structure affected by the conflict. This rejection of  
15 the operations is not necessary for operations of the changeProperty() type (HK6, HK4) which overwrite one another, because the operation created with the new state overwrites the old operations directly.

20 For a conflict with an operation defining the conflict from the set of data operations (conflicts of the types HK3, HK6, HK7 I, HK8 I and HK9), for a conflict with a plurality of operations defining the conflict from the set of data operations in the case of just one copy database (conflicts of the types HK5, HK7 II, HK8 II,  
25 HK11) and for a conflict with at least one operation defining the conflict from the set of data operations in the case of the two copy databases (conflicts of the types KK1, ..., KK8), there is the following resolution option, which is called the sixth decision option E6.

30

The sixth decision option E6 describes the rejection of the conflict operation(s) and selection of new operation(s).

35 In this context, to change a relationship (KK2) on both sides or to change an entry in an ordered listing (KK7) on both sides, the rejection, in contrast to the second decision option E2 (rejection of all operations), relates only to the creator operations for the new

10220 04204 0220 0220

- relationships or for the new entries. The common deletion operation for the old relationship or for the old entry remains unaffected. For the third critical conflict KK3 and the eighth critical conflict KK8, the sixth decision option E6 has the option only of changing the createRelationship or the changePropertyInsert operation. The common deletion operation remains unaffected.
- 10 For the definition of a new state for a conflict of type HK7, HK8 or KK5, the number of changePropertyAdd operations and changePropertyDel operations is likewise described with i and k
- 15 (i if changePropAdd operations are involved and k if changePropDel operations are involved).

- For the selection of a new state and the creation of the operations necessary for this, interactions on the surface of the application program are customary. If the option exists of selecting a new state using only a complex interaction and if the operations created by the interaction also affect other, unresolved conflicts, then there is the option
- 20 a) of using the decision set to resolve the other affected conflicts as well, or
- 25 b) of shifting creation of the new state to a later instant, i.e. after reintegration and during the coupled further work.

- 30 If, in accordance with a), other affected conflicts are likewise to be resolved, then it is first necessary to reject the operations of the conflict set if conflicts of the type HK6 and KK4 are involved and the operations
- 35 are not operations which overwrite one another.

**Figure 4** shows the decision sets ES1, ES2, ES3, ES4, ES5, ES6, ES7, ES8, ES9, ES10, ES11, ES12, ES13, ES14,

ES15, ES16, ES17, ES18, ES19, ES20, ES21, ES22, which are allocated to the respective conflicts.

5 The sixth harmless conflict HK6 is allocated a sixth decision set ES6, containing the first decision option E1, the second decision option E2 and the sixth decision option E6.

10 A twelfth decision set ES12 is allocated to the first critical conflict KK1. The twelfth decision set ES12 contains four possible decisions, the second decision option E2, the first part E3a of the third decision option E3, the second part E3b of the third decision option E3 and the sixth decision option E6.

15 The further decision sets are shown in Figure 4 and will be illustrated below for purposes of simplification with the aid of the following list:

- 20 • The first harmless conflict HK1, the second harmless conflict HK2, the fourth harmless conflict HK4 and the tenth harmless conflict HK10 are allocated respective decision sets comprising the first decision option E1 and the second decision option E2.
- 25 • The third harmless conflict HK3, the fifth harmless conflict HK5, the sixth harmless conflict HK6, the first type HK7 I of the seventh harmless conflict HK7, the first type HK8 I of the eighth harmless conflict HK8, the ninth harmless conflict HK9 and the
- 30 eleventh harmless conflict HK11 are allocated respective decision sets containing the first decision option E1, the second decision option E2 and the sixth decision option E6.
- 35 • The second type HK7 II of the seventh harmless conflict HK7, the second type HK8 II of the eighth harmless conflict HK8, the first critical conflict KK1, the second critical conflict KK2, the third critical conflict KK3, the fourth critical conflict KK4, the first type KK5 I of the fifth critical

102210" 524459

conflict KK5, the sixth critical conflict KK6, the seventh critical conflict KK7 and the critical conflict KK8 are allocated respective decision sets containing the second decision option E2, the first part E3a of the third decision option E3, the second part E3b of the third decision option E3 and the sixth decision option E6.

- The second type KK5 II of the fifth critical conflict KK5 is allocated a decision set having six possible decisions, the second decision option E2, the first part E3a of the third decision option E3, the second part E3b of the third decision option E3, the first part E5a of the fifth decision option E5, the second part E5b of the fifth decision option E5 and the sixth decision option E6.
- The second type HK7 II of the seventh harmless conflict HK7 and the second type HK8 II of the eighth harmless conflict HK8 are each allocated a decision set having four possible decisions, the first decision option E1, the second decision option E2, the fourth decision option E4 and the sixth decision option E6.

#### **Restrictions on decision options**

It should be noted that the correct execution of individual decisions is dependent on the presence of a data element or of a plurality of data elements in the two copy databases.

By way of example, for adoption in the case of the third harmless conflict HK3A, the two data elements denoted by means of their identifiers in the relationship operation in conflict must also be present in the copy database of the user B. If one of the data elements is missing, or indeed if both are missing, then this decision about adoption of the operation is not possible.

It is thus evident that dependencies may exist between individual conflicts.

- 5 A dependency of a conflict on conflicts of the type HK1A, HK1B, HK2A or HK2B in terms of its decision options is defined as follows:

**Dependent conflict:**

- 10 A conflict is dependent on the first harmless conflict HK1 or on the second harmless conflict HK2 if its decision options are restricted by the presence of a first harmless conflict HK1 or of a second harmless conflict HK2.

- 15 A dependency AK of a conflict is defined as follows:

**Dependency AK of a conflict:**

- 20 A dependency AK of a conflict K1(EHA, EHB, GH) on a conflict K1(EHA, EHB, GH) is a 4-tuple

AK (K1, K2) def (id, ctype, cid1, cid2)

- id is a one-to-one identifier throughout the system (see also definition of a data element)
- 25 • ctype  $\in$  {HK1A, HK1B, HK2A, HK2B}
- cid1 = K1.id
- cid2 = K2.id.

- 30 A dependency register AKR is defined as follows:

**Dependency register AKR:**

A dependency register AKR for two histories EHA and EHB and a common history GH is a 1-tuple

- 35 AKR (EHA, EHB, GH) def (dependencyids)

- dependencyids are the identifiers for all recognized dependencies of the histories EHA and EHB and the common history GH.

20250423 10:22:23



All restrictions on decision options by existing conflicts of the first harmless conflict HK1 and of the second harmless conflict HK2 are recognized and marked at the start of conflict resolution on the basis of the dependencies AK.

This is done using the decision restrictions' parameter introduced in the conflict definition for each conflict. All the possible restrictions are described below.

The first harmless conflict HK1 impairs the decision options for conflicts with operations within the dedicated history. These dependent conflicts include all those containing a createRelationship operation or a property change with the created data element. In this context, in the case of harmless conflicts HK6, ..., HK11 with property operations for this data element, the decisions are minimized by an adoption and a creation of a new state.

The decision options for the critical conflicts KK1, KK2 and KK3 with relationship operations with the created data element are reduced by the option of adopting the operations (-E3a, -E3b) for the copy database whose history contains the createElement operation. The decision options for the third harmless conflict HK3 and the fifth harmless conflict HK5 with relationship operations with the created data element are reduced by the decision to accept and/or create a new state. Critical conflicts with property operations experience no modifications to their decision collection (decision sets).

A second harmless conflict HK2 impairs the decision option for conflicts in the two copy databases. The harmless conflicts for modifying properties HK6, ..., HK11 are treated as for the first harmless conflict HK1. The harmless conflicts with relationship

operations (HK4, HK5) in the history of the deleteElement operation no longer have any decision option for rejection and the decisions relating to the harmless relationship conflicts in the other copy database HK3, HK5 are minimized by the option of accepting and/or creating a new state. The critical conflicts with relationship operations in the copy database without the deleteElement operation are reduced by the option resetting and/or adopting the operations. Critical conflicts with property operations experience no modification to their property collection in this case either.

A common deleteElement operation contained in the common history GH and representing no conflict reduces the decision options in specific cases. Thus, all critical conflicts KK2 and KK3 with relationship operations in which the target data element of the common deleteRelationship operation corresponds to the data element deleted on both sides can no longer be reset.

Dependent conflicts with one or more relationship operations (HK3, HK4, HK5, KK1, KK2, KK3), i.e. with a plurality of listed identifiers and hence a plurality of data elements involved, can have a plurality of dependencies at the same time. In this regard, there may be just one dependency for each arising identifier in a conflict. A dependent conflict having a plurality of identifiers can firstly have a plurality of dependencies on conflicts of the same conflict type (for example on two conflicts of the first harmless conflict HK1a) and can secondly have a plurality of dependencies on conflicts of different conflict types (e.g. on a conflict of the type HK1a and on a conflict of the type HK1b). By way of example, a dependent conflict of the type HK3a can have two dependencies on two conflicts of the type HK1a, namely one with the identifier id1 and one with the identifier id2. At the

same time, the second critical contact KK2 can have a dependency on the second harmless conflict HK2a, on the first harmless conflict HK1a and on the first harmless conflict HK1B.

5

The dependency of the identifiers for a conflict of the type HK1 or HK2 means that there can be a maximum of three restrictions per conflict of the type HK5, KK1, KK2 or KK3. All conflicts of the type HK3A, HK3B, HK4A, HK4B, HK5A and HK5B can have a plurality of dependencies on conflicts of the same or different type at the same time. Conflicts of the types KK1, KK2, KK3A and KK3B, on the other hand, can have a plurality of dependencies on conflicts of different types at the same time. However, the same restrictions of the decision options may also arise a number of times for conflicts which have a number of dependencies on the same conflict type. Thus, for a conflict of the type HK3A, two dependencies are possible at the same time in the presence of a conflict of the type HK1A or of one of the type HK2B and the decisions are each minimized by the first decision E1.

The multiple restrictions arising for many dependent conflicts with the same decision options do not require any separate consideration. Each of these decision restrictions is considered as if it were an individual, specific limitation. Hence, all multiple restrictions, like others as well, are noted in the conflict. If a conflict of the type HK1 and HK2 is resolved such that one of the restrictions arising a number of times is eliminated, the rest of these restrictions are retained. Only when different conflict resolutions mean that there are no longer any of the multiple restrictions present can a decision of this type be made. This applies irrespective of whether the restriction was present once or a plurality of times.

The restrictions, recognized once at the start of reintegration, as a result of dependencies of the conflicts on conflicts of the type HK1 and HK2 are changed dynamically depending on the resolution of the conflicts of the type HK1 and HK2 during the reintegration. Thus, depending on the type of the dependent conflicts and on the respective resolution decision for the createElement operation and deleteElement operation, the following changes to the decision restrictions result:

- a) The adoption of a createElement operation (first decision E1 relating to a conflict of the type HK1) causes the decision restrictions to be reset, i.e. the decision options to be extended, for all conflicts dependent on the operation.
- b) The rejection of a deleteElement operation (second decision E2 relating to a conflict of the type HK2) likewise causes the decision restrictions to be reset, i.e. the decision options to be extended for the conflicts dependent on this conflict.
- c) The rejection of a createElement operation (second decision E2 relating to a conflict of the type HK1) causes the decision restrictions already made for the conflicts dependent on this conflict to be retained. Hence, no decision options change.
- d) The adoption of a deleteElement operation (first decision E1 relating to a conflict of the type HK2) causes the decision restrictions already made for the conflicts dependent on this conflict to be retained. Hence, no decision options change.

An anomaly created on one side can be recognized by means of two respective conflicts present in a history. In this context, there are the options of the conflict pairs HK5Aa/HK5Ab, HK4A/HK3A, HK4A/HK5A. In the case of a conflict of the type HK5Aa, the deleteRelationship operation is involved in the anomaly and in the case of a conflict of the type HK5Ab, the createRelationship operation is involved in the anomaly.

For anomalies arising on account of modifications on the copy database of the second user B, the same options apply: HK5Ba/HK5Bb, HK4B/HK3B, HK4B/HK5B. In this context, a common feature of all conflict pairs is that there is a deleteRelationship operation with an identifier id1 as source data element and with an identifier id2 as target data element in one of the two conflicts and the same identifiers arise in reverse as source data element and target data element in a createRelationship operation for the other conflict.

The adoption of the conflict of the one-sided anomaly, as described above, with the createRelationship operation prevents rejection of the conflict of the one-sided anomaly with the deleteRelationship operation for a rejection of the conflict of the one-sided anomaly with the deleteRelationship operation, but on the other hand prevents adoption of the conflict of the anomaly with the createRelationship operation. The change in one of the two conflicts does not reduce the decision options for the other conflict.

The result of this is that an anomaly created on one side in directed relationships can be resolved by rejecting the two conflicts, adopting the two conflicts, changing the two conflicts differently or modifying one of the conflicts and adopting or rejecting the other conflict.

An anomaly created on both sides in directed relationships can be resolved by deciding one of the two conflicts and deciding the other conflict in a different manner from this.

To prevent an anomaly (so-called pseudo-anomaly) from arising, as described above, the following restrictions on the decision options are provided:

0044335 04304

5 a) After adoption of a conflict with the  
createRelationship operation containing the common  
data element id1 as target data element  
(createRelationship21), there must no longer be, for  
the conflict with the two createRelationship  
operations containing the common data element as  
source data element, any decision option of the  
sixth decision option E6 with replacement of the  
target data element (idx or idz) by the source data  
10 element id2(createRelationship21).

15 b) After a sixth decision E6 has been made on the basis  
of the sixth decision option E6 and selection of a  
new target data element id2 for the conflict with  
the two createRelationship operations containing the  
common data element id1 as source data element, no  
further adoption of the conflict with the  
createRelationship operation with the common data  
element id1 as target data element  
(createRelationship21) must be possible.

20

As described above, as part of this method, the  
decision options for conflicts are limited on the basis  
of their dependencies, anomalies and pseudo-anomalies.

25 After each decision relating to a conflict, a change to  
the decision options for the conflicts which are  
dependent on the conflict just resolved or are situated  
in a common anomaly or pseudo-anomaly with this  
conflict is made on the basis of the dependencies,  
30 anomalies and pseudo-anomalies.

A decision is made for each conflict, as described  
above. The decision can be made in different ways. An  
overview of possible decision variations can be found  
35 in [1].

Within the scope of this illustrative embodiment,  
provision is made for a database or copy database to be  
regarded as a reference database, and for the

adjustment to be carried out on the basis of the reference database.

Thus, as shown in Figure 1 by means of a recursive loop  
5 via a checking step (step 105), a check is made to  
determine whether there is still any conflict and  
whether a decision thus needs to be made. If a decision  
is still to be made, then it is made. If there are no  
more conflicts present, then a last method step (step  
10 106) is carried out, storage of the reintegrated  
database, which contains no more inconsistencies.

The inconsistency-free database is again transmitted to  
all further computers connected to the first computer  
15 200 (step 107).

All the computers therefore have a consistent copy  
database.

20 The following text illustrates a few alternatives to  
the illustrative embodiment described above:

Inconsistencies can also be recognized after a  
prescribable number of elimination operations carried  
25 out for an inconsistency by searching for a further  
inconsistency. This can be extended such that, each  
time an inconsistency has been eliminated, a subsequent  
inconsistency is again sought and eliminated.

30 It is also possible for the first computer to use the  
method illustrated above to ascertain a series of  
correction commands (correction sequences) which is  
respectively transmitted to the computer whose copy  
database has been checked for inconsistencies, and for  
35 the respective computer to use the correction sequence  
to adjust its copy database to the database.

In addition, in one alternative embodiment, it is  
likewise possible to leave the decision to a user or to

2011 RELEASE UNDER E.O. 14176

a plurality of users, i.e. the decision options are displayed to a user on the screen and the user uses the keyboard or the computer mouse to select the decision he requires, which is then implemented by the computer.



